



Sewer OB Junction Clamps (CBJ)



Rapid Sewer OB Junction clamps are made from 316 Stainless Steel, they are ideally suited for new or damaged property connections on non-pressure sewer pipelines designed for a permanent sewer branch.

They are made to provide the same quick-and-easy Rapid fitting qualities. All of the Rapid Sewer Junction Clamps are made using AS 4181 requirements* and in accordance with ISO 9001 quality standards. They provide a simple and permanent way of connecting branch off-takes to new, broken, and renewed/re-lined sewer pipes. The standard sewer clamps come with the off- take branch at 45 degrees, and has an uPVC access coupling secured to it for solvent welded connections to uPVC pipes. The sewer clamps are made to adapt to pipe ovality and irregularities. With a fully lined rubber gasket, damaged pipes can be easily rehabilitated.

Sizes range from DN 150 to DN 600mm, with off takes sizes DN 100 and DN 150mm. (Depending on host pipe)
Operating pressure from -80kPA to 100kPA. Max. temp. 60 degrees C.

COMMON RAPID OB SEWER CLAMPS

PART NO	OD RANGE	DESCRIPTION
CBJ-160/170-100	160 - 170	OB SS316 CLAMP 160 to 170 x 100 x 45 uPVC
CBJ-170/180-100	170 - 180	OB SS316 CLAMP 170 to 180 x 100 x 45 uPVC
CBJ-190/210-100	190 - 210	OB SS316 CLAMP 190 to 210 x 100 x 45 uPVC
CBJ-190/210-150	190 - 210	OB SS316 CLAMP 190 to 210 x 150 x 45 uPVC
CBJ-225/245-100	225 - 245	OB SS316 CLAMP 225 to 245 x 100 x 45 uPVC
CBJ-225/245-150	225 - 245	OB SS316 CLAMP 225 to 245 x 150 x 45 uPVC
CBJ-250/270-100	250 - 270	OB SS316 CLAMP 250 to 270 x 100 x 45 uPVC
CBJ-250/270-150	250 - 270	OB SS316 CLAMP 250 to 270 x 150 x 45 uPVC
CBJ-310/330-100	310 - 330	OB SS316 CLAMP 310 to 330 x 100 x 45 uPVC
CBJ-310/330-150	310 - 330	OB SS316 CLAMP 310 to 330 x 150 x 45 uPVC
CBJ-395/415-100	395 - 415	OB SS316 CLAMP 395 to 415 x 100 x 45 uPVC
CBJ-395/415-150	395 - 415	OB SS316 CLAMP 395 to 415 x 150 x 45 uPVC

Other and larger sizes available.

*AS4181 pressure testing requirements reduced

E. & O.E.